Plant Archives Vol. 22, No. 1, 2022 pp. 421-424 e-ISSN:2581-6063 (online), ISSN:0972-5210

Plant Archives

Journal homepage: http://www.plantarchives.org
DOI Url : https://doi.org/10.51470/PLANTARCHIVES.2022.v22.no1.065

SCHEDULING OF DRIP IRRIGATION SYSTEM FOR GARLIC CROP IN MALWA REGION OF MADHYA PRADESH, INDIA

Rajesh Gupta[1*], G.S. Kulmi[2] and Ajeet Sarathe[3]
[1]Scientist, RVSKVV-KVK, Mandsaur (M.P.)
[2]Sr. Scientist & Head, RVSKVV-KVK, Mandsaur (M.P.)
[3]Assistant Professor, AKS University, Satna (M.P.)
*Correspondence Author E-mail: rajgupta171@gmail.com
(Date of Receiving : 12-01-2022; Date of Acceptance : 30-03-2022)

ABSTRACT

The field experiments were conducted during the two consecutive rabi seasons 2017-18 and 2018-19 at farmer's field to study the influence of drip irrigation on plant growth and yield parameters of garlic (cv. G-282) in Gogarpura village of Mandsaur district of Madhya Pradesh. The experiment was laid out in a factorial randomized block design with nine treatment combinations consisting of three irrigation levels and three fertilizer levels having three replications and one control plot treatment of flood irrigation in border strip. Three irrigation levels were 60% CPE, 80% CPE and 100% CPE. The maximum percentage of water saving over control treatment was observed in treatment 60% CPE (63.93%) followed by 80% CPE (51.90%) and 100% CPE (39.88%). The irrigation levels significantly affected ($P<0.05$) the plant height, marketable bulb yield and gross bulb yield of garlic. However, the neck thickness was not affected by irrigation levels. Highest plant height (73.01 cm), neck thickness (0.84 cm), marketable bulb yield (115.23 q/ha) and gross bulb yield (126.75 q/ha) was recorded in treatment 100% CPE.

***Keywords* :** Garlic, Drip Irrigation, Plant height, Marketable bulb yield, Gross bulb yield

Introduction

Garlic (*Allium sativum* L.) belongs to the family Alliaceae. India has become one of the biggest exporters of garlic worldwide. It is used as a spice or condiment throughout India and also an important foreign exchange earner for India and grown in large quantities in the states of Madhya Pradesh, Gujarat, Orissa, Rajasthan, Karnataka, Tamil Nadu, Maharashtra and Bihar. Madhya Pradesh is leader state in the production of seed spices and the largest producer of garlic in India and occupies the area of over 81.17 thousand ha with a production of 424.50 thousand MT (NHRDF, 2017). Garlic is a very shallow-rooted bulb crops and very sensitive to moisture stress conditions particularly during bulb initiation and development. Frequent irrigation is, therefore, necessary for better bulb development. In garlic, flood irrigation is widely practiced in India, which results in inefficient use of irrigation water due to losses in deep percolation, distribution and evaporation. The drip irrigation technology is the key intervention in water and fertilizer saving which enhanced the crop productivity. Reduced evaporative losses and high irrigation uniformity of surface drip system often results in high irrigation application efficiencies (Schwankl *et al.*, 1996). Energy requirements and costs may be less for low-pressure drip irrigation systems than for high-pressure systems such as impact sprinklers. This system applies water slowly, almost matching with the consumptive use by the plant, to keep the soil moisture within the desired range of available moisture to plant growth and minimizes the water losses in the conventional irrigation methods such as percolation, runoff and evaporation. The area between the crop row is not irrigated therefore more area of land can be irrigated with the same amount of water. Thus, water saving and production per unit of water is very high in drip irrigation. Drip irrigation is making a positive impression on sustainable agriculture in India. Studies conducted on irrigation methods at Directorate of Onion and Garlic Research, ICAR, Pune revealed that the drip irrigation at 100 percent CPE (cumulative pan evaporation) recorded the highest marketable bulb yield in garlic crop with 30-40 percent water saving in comparison with surface irrigation (Sankar *et al.,* 2008).

In Malwa region of Madhya Pradesh, garlic is considered as one of the major rabi crop especially in Mandsaur district and most of the garlic growers practiced flood irrigation which resulted in less productivity. Therefore, this study was conducted to optimise the irrigation scheduling for garlic crop under drip irrigation in agro-climatic conditions of Malwa region of Madhya Pradesh.

Materials and Methods

The field experiments were conducted during the two consecutive rabi seasons 2017-18 and 2018-19 at farmer's field to study the influence of drip irrigation on plant growth and yield parameters of garlic (cv. G-282) in Gogarpura village of Mandsaur district of Madhya Pradesh. The area is situated in western part of Madhya Pradesh which falls under agro-climatic zone of Malwa plateau. It lies between the parallels of 23°45'50" and 25°2'55" north latitudes and between the meridians of 74°42'30" and 75°50'20" east longitudes with an average elevation of 436 meters. Mandsaur belongs to sub-tropical climate having a mean temperature range of minimum 50^0C and maximum 44^0C in winter and summer, respectively. The average annual rainfall in the district is 786.6 mm. The topography of the experimental site was uniform and leveled and the soil is clayey in texture with 45 cm depth. A composite soil sample from 15 cm soil layer was collected before the start of experiment for analyzing the various physico-chemical properties of soil. The experiment was laid out with nine treatment combinations consisting of three irrigation levels and three fertilizer levels having three replications and one control plot treatment of flood irrigation in border strip. Three irrigation levels (treatments) were 60% CPE, 80% CPE and 100% CPE.

The total plot size of experimental site was 35 m X 25 m with individual plot area of 15 m X 1.2 m. The garlic cloves were dibbled at 15 cm X 10 cm spacing on broad bed furrow (BBF) of 120 cm top width with 45 cm furrow maintaining 15 cm height. Each BBF having two drip laterals with in-built emitters with 50 cm spacing between two consecutive emitters at a discharge rate of 4.1 lph. The uniformity coefficient was calculated as 96.80% at pressure of 1.0 kg/cm^2. Irrigation water was applied according to daily crop evapotranspiration. In this study, a fixed irrigation interval of three days was adopted and amount of water applied was estimated based on previous two days evapotranspiration. The irrigation was stopped 15 days before harvesting in all treatments. The meteorological data like rainfall, minimum and maximum temperature, relative humidity, wind speed and sunshine hours, during crop growth period were collected from automatic weather station of College of Horticulture, Mandsaur located at nearby experimental site. The observation on plant height, neck thickness, gross bulb yield and marketable bulb yield of garlic were recorded using standard procedures. The experiment was laid out in factorial randomized block design (FRBD) with three replications as suggested by Gomez and Gomez (1984).

Results and Discussion

In different irrigation treatments the total quantity of water applied for both the experimental years is presented in Table 1. The irrigation water applied in treatment 100% CPE was maximum (345.01 mm) followed by 80% CPE (276.01 mm) and 60% CPE (207.01 mm) in first year of experiment (2017-18), similarly, it was maximum in 100% CPE (350.54 mm) followed by 80% CPE (280.43 mm) and 60% CPE (210.32 mm) in second year of experiment (2018-19). Whereas, maximum amount of irrigation water was applied as 573.76 mm and 583.09 mm in control treatment i.e., border strip method of flood irrigation during the first year and second year of experiment respectively. The maximum percentage of water saving over control treatment was observed in treatment 60% CPE (63.93%) followed by 80% CPE (51.90%) and 100% CPE (39.88%). The present findings are supported by Patel *et al*. (1996), Mohammad and Zuraiqi (2003), Sankar *et al*. (2008) and Chala and Quraishi (2015).

The results revealed that plant height was significantly affected by different irrigation treatments (Table 2). The plant height was significantly higher (73.01 cm) in 100% CPE followed by 80% CPE (72.57 cm), control (71.01 cm) and least in 60% CPE (69.39 cm). The increased plant height in drip irrigated treatments might be due to better availability of moisture and nutrients near root zone during entire crop growth period which favoured the growth attributes. Similar results were obtained by Sankar *et al*. (2008) and Mahadeen (2011). The neck thickness was unaffected by irrigation levels (Table 2), however drip irrigated treatments gave higher neck thickness as compared to control. The highest neck thickness was recorded in 100% CPE (0.84 cm) followed by 80% CPE (0.78 cm) and least in control (0.68 cm) as given in Table 2.

The result showed that the different grade garlic bulbs viz., A-Grade (>25 mm), B-Grade (15-25 mm), C-Grade 10-15 mm), D-Grade (<10 mm) were significantly affected by different irrigation treatments. The A, B and C grade bulbs were considered under marketable yield and D grade bulbs considered under unmarketable category (Table 3). The pooled data clearly indicated that the 100% CPE gave the lowest percentage (8.83%) of unmarketable bulb yield and whereas control treatment gave the highest percentage (12.54%) of unmarketable bulb yield. This might be due to the fulfilment of crop nutrient and water requirement at various growth stages under different irrigation treatments. It is evident fact that drip irrigation ensures better aeration and moisture in the root zone (Tiwari *et al*., 2003). These results are in accordance with Sankar *et al*. (2008) in garlic and Enchalew *et al.* (2016) in onion.

The yield of garlic bulb was significantly affected by different irrigation levels (Table 4). Marketable bulb yield of garlic was found maximum in 100% CPE (115.23 q/ha) which was significantly higher over control (71.05 q/ha), 60% CPE (102.17 q/ha) and 80% CPE (108.51 q/ha). Similarly, gross bulb yield of garlic was found maximum in 100% CPE (126.75 q/ha) which was significantly higher over control (80.38 q/ha), 60% CPE (113.42 q/ha) and 80% CPE (119.85 q/ha) as given in Table 4. These results are in line with that of Patel *et al*. (1996) and Ayars (2008). The maximum bulb yield was recorded in treatment 100% CPE may be due to the favourable effect of available soil moisture, uniform distribution of irrigation water and fertilizers in split doses during entire growth period of garlic. Also, drip irrigation treatment created better micro-climate as compared to flood irrigation because of prolonged duration of watering.

Conclusion

Based on the two years rabi season experiment,, it can be concluded that the 100% CPE (cumulative pan evaporation) with three days irrigation interval was found best in order to get higher marketable and gross bulb yield for agro-climatic conditions of Malwa plateau of Madhya Pradesh.

Table 1: Quantity of water applied in different irrigation treatments

Irrigation levels	Irrigation water (mm)			Water saving (%)
	2017-18	2018-19	Average	
60% CPE	207.01	210.32	208.67	63.93
80% CPE	276.01	280.43	278.22	51.90
100% CPE	345.01	350.54	347.78	39.88
Control	573.76	583.09	578.43	-

Table 2: Plant growth parameters of garlic as influenced by different irrigation levels

Parameter	Year	60% CPE	80% CPE	100% CPE	Control	CD (0.05)
Plant height (cm)	2017-18	69.03	72.48	73.15	70.94	0.12
	2018-19	69.75	72.66	72.87	71.08	0.13
	Pooled	69.39	72.57	73.01	71.01	S
Neck thickness (cm)	2017-18	0.71	0.77	0.83	0.67	0.02
	2018-19	0.73	0.79	0.85	0.69	0.03
	Pooled	0.72	0.78	0.84	0.68	NS
S - Significant, NS - Non Significant						

Table 3: Garlic yield of different grades as influenced by different irrigation levels

Treatment	Grade wise bulb yield (q/ha)				Market-able bulb yield (q/ha)	Gross bulb yield (q/ha)	Unmar-ketable Yield (%)
	Grade A	Grade B	Grade C	Grade D			
Year: 2017-18							
60% CPE	26.49	37.73	37.19	11.02	101.41	112.43	9.80
80% CPE	28.59	39.79	39.31	11.01	107.69	118.7	9.28
100% CPE	30.71	42.72	41.44	11.12	114.87	125.99	8.83
Control	17.79	26.14	26.73	10.13	70.66	80.79	12.54
Year: 2018-19							
60% CPE	27.06	38.18	37.69	11.47	102.93	114.4	10.03
80% CPE	28.8	40.34	40.19	11.67	109.33	121	9.64
100% CPE	30.85	42.96	41.77	11.92	115.58	127.5	9.35
Control	17.99	26.32	27.12	10.53	71.43	81.96	12.85
Pooled							
60% CPE	26.77	37.95	37.44	11.24	26.77	37.95	37.44
80% CPE	28.69	40.06	39.75	11.33	28.69	40.06	39.75
100% CPE	30.77	42.83	41.6	11.52	30.77	42.83	41.60
Control	17.89	26.23	26.92	10.33	17.89	26.23	26.92

Table 4: Gross and Marketable bulb yield of garlic as influenced by different irrigation levels

Parameter	Year	60% CPE	80% CPE	100% CPE	Control	CD (0.05)
Marketable bulb yield (q/ha)	2017-18	101.41	107.69	114.87	70.66	2.73
	2018-19	102.93	109.33	115.58	71.43	2.38
	Pooled	102.17	108.51	115.23	71.05	S
Gross bulb yield (q/ha)	2017-18	112.43	118.70	125.99	80.79	2.01
	2018-19	114.40	121.00	127.50	81.96	1.96
	Pooled	113.42	119.85	126.75	81.38	S
S - Significant						

References

Ayars, E.J. (2008). Water requirement of irrigated garlic. *Transactions of the ASABE*, 51(5): 1683-1688.

Chala, M. and Quraishi, S. (2015). Effect of deficit irrigation on yield and water productivity of garlic (*Allium sativum* L.) under drip irrigation and mulching at Wolaita Soddo, Ethiopia. *International Journal of Life Sciences*, Vol. 4 (4): 232-239.

Enchalew, B., Gebre, S.L., Rabo, M., Hindaye, B. and Kedir, M. (2016). Effect of deficit irrigation on water productivity of onion (*Allium cepa* L.) under drip irrigation. *Irrigation Drainage Sys Eng.,* 5: 172. doi: 10.4172/2168-9768.1000172.

Gomez, K.A. and Gomez, A.A. (1984). Statistical procedures for agricultural research, 2nd Ed. New York. John Wiley and Sons.

Mahadeen, A.Y. (2011). Influence of clove weight on vegetative growth and yield of garlic (*Allium sativum* L.) grown under drip irrigation. *Jordan Journal of Agricultural Sciences*, 7(1): 44-48.

Mohammad, M.J. and Zuraiki, S. (2003). Enhancement of yield and nitrogen and water use efficiencies by nitrogen drip fertigation of garlic. *Journal of Plant Nutrition*, 26(9): 1749-1766.

NHRDF (2017). National Horticultural Research and Development Foundation. http://www.nhrdf.com

Patel, B.G., Khanpara, V.D., Malavia, D.D., Maraviya, R.B. and Kaneria, B.B. (1996). Economic feasibility of drip irrigation in garlic. *Ind. J. Agron.*, 45: 143-145.

Sankar, V., Lawande, K.E. and Tripathi, P.C. (2008). Effect of micro irrigation practices on growth and yield of garlic (*Allium sativum* L.) var. G. 41. *Journal of Spices and Aromatic Crops*, 17(3): 230-234.

Schwankl, L.J., Edstrom, J.P., and Hopmans, J.W. (1996). Performance of micro-irrigation systems in almonds. *Proc. Seventh International Conference on Water and Irrigation*. Tel Aviv, Israel, pp. 123-132.

Tiwari, K.N., Singh, A. and Mal, P.K. (2003). Effect of drip irrigation on yield of cabbage *(Brassica oleracea* L. Var. capitata*)* under mulch and no mulch conditions. *Agricultural Water Management,* 58: 19-28.